

MOTIP Black Oil

Ord.-no.: 090300

Technical Information



Prevent wear and sticking of screwed connections exposed to heavy workloads with MOTIP Black Oil. Black Oil is water repellent, prevents corrosion, and is resistant to the weather, weak acids and bases. It has a precise jet-spray and a 360° valve.

Quality & properties

- Prevents wear and sticking
- Excellent corrosion prevention
- Water-repellent
- Excellent adhesion
- Resistant to weather influences
- 360° valve
- Resistant to weak acids and bases
- Directed jetspray

Physical & chemical data

- Base: Bitumen with polyisobutene
- Colourname: transparent brown
- Smell: Characteristic
- Surfaces: Agricultural machinery, Industrial machinery, Truck, Cross country motorcycle, Off the road vehicle
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,8
- Vapour pressure: 3500/20 bar
- Relative density: 0.92 g/ml
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Spray parts to be treated prior to assembly. After evaporation a protective film remains, which simplifies the future disassembly.
- The protective film can be removed with MOTIP Industrial Cleaner.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.