

## MOTIP Effect Metallic

Ord.-no.: look at ordering information

## Technical Information



Fast-drying lacquer to treat surfaces of wood, metal, aluminium, glass, stone and various types of plastic. Metallic Lacquer is rub resistant, scratch free and wear-resistant and resistant to weather influences. MoTip Deco Effect Metallic Lacquer is available in 13 colours.

### Quality & properties

- Fast drying
- Rub resistant
- Non-fading and UV resistant
- Scratch free and shock proof
- Resistant to weather influences
- Scratch free and wear-resistant
- Excellent adhesion

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - ◊ brilliant silver
  - ◊ aluminium
  - ◊ sparkling silver
  - ◊ silver
  - ◊ gold
  - ◊ brilliant gold
  - ◊ real gold
  - ◊ antique gold
  - ◊ blue
  - ◊ black
  - ◊ red
  - ◊ violet
  - ◊ green
- Efficiency: – 1,25 - 1,75 m<sup>2</sup>
- Dry to touch: 10 - 20 min
- Dust dry: 5 - 10 min
- Completely dry: 120 min
- Overcoatable: 120 min
- Surfaces:
  - ◊ wood, metal, aluminium, glass, stone and various types of plastic
  - ◊ wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure:
  - ◊ 4000/20 bar
  - ◊ 3500/20 bar
  - ◊ 13/20 bar
- Flash point:
  - ◊ n.a. °C
  - ◊ 27 °C
- Temperature Resistance: – 110 °C
- Content: 12 ML

### How to use

- The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of June 10, 2022** – This release replaces all eventually earlier issued versions.

**European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)**  
**European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)**