

MOTIP Anti-Corrosion Primer

Ord.-no.: 090106

Technical Information



Protect steel parts and machines with MOTIP Anti-Corrosion Primer. Suitable as pre-treatment for topcoating with air drying alkyd resin varnishes. Fast-drying, lead-free red oxide primer to treat untreated surfaces of ferro-metal. Suitable as pre-treatment for respraying with air drying alkyd lacquer systems. Anti-corrosion primer has excellent coverage, filling properties and adhesion. MOTIP Anti Corrosion is weldable and easy to sand and has excellent corrosion prevention.

Quality & properties

- Excellent coverage and filling properties
- Easy to sand
- Excellent corrosion prevention
- Suitable to protect wood
- Weldable
- Excellent adhesion
- Misty spray pattern
- Fast drying

Physical & chemical data

- Base: Epoxy modified alkyd resin
- Colourname: red brown
- Dry to touch: 30 - 60 min
- Dust dry: 10 - 20 min
- Surfaces: Steel Constructions, Machinery, Agricultural Machinery, Bodywork, Containers, Steel frames
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,0
- Vapour pressure: 3500/20 bar
- Relative density: 1.4 g/ml
- Storage stability: 10 y
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The aerosol should have room temperature. Best processing temperature 5 to 30°C.
- Before use, shake the aerosol for 2 minutes and spray a sample.
- Distance to the surface to be treated approximately 20 centimetre.
- Apply anti corrosion primer in several layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 9, 2022 – This release replaces all eventually earlier issued versions.

