

## MOTIP Cable Anti-Friction Spray

Ord.-no.: 090208

### Technical Information



Facilitates pulling of cables and wires in electrical installation pipes. Breaks, cracks and the clamping of the cable can be prevented. Suitable for all types of cables.

#### Quality & properties

- Suitable for all types of cables
- Does not attack rubber, plastics, textiles and lacquers
- Reduces friction
- Water-repellent
- Does not stick or dry out

#### Physical & chemical data

- Base: Special resin
- Colourname: no colour
- Surfaces: Electric wire and cables
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Dielectric strength: 12 kv/mm
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content: 500 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the spray directly onto the cable or with the spray probe into the line inlet.
- Then pull the cable.
- During installation, spray cables or wires in sections.
- Attention: MOTIP Cable Anti-Friction Spray can cause high smoothness in the working environment. Clean and economical processing; Do not spray on floors, tiles, laminate or other treads.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 16, 2024 – This release replaces all eventually earlier issued versions.