

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name: **Motip Industrial 2K Epoxy Clear coat highgloss**

Article number: 04132

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

Product category PC9a Coatings and paints, thinners, paint removers

##### Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Clear coating material, Varnish

##### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

Further information obtainable from: Department Product Safety

##### 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



corrosion

Eye Dam. 1 H318

Causes serious eye damage.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 1)



Skin Irrit. 2 H315

Causes skin irritation.

Skin Sens. 1 H317

May cause an allergic skin reaction.

### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### · Hazard pictograms



GHS02



GHS05



GHS07

#### · Signal word Danger

#### · Hazard-determining components of labelling:

iso-butanol

Bisphenol (Epoxy Resin)

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

butan-1-ol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 2)

<b>· Dangerous components:</b>		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 ⚠ Press. Gas (Comp.), H280	25-<50%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	10-<12.5%
CAS: 25036-25-3 EC number: 682-390-8	Bisphenol (Epoxy Resin) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<12.5%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23	iso-butanol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	2.5-<5%
CAS: 68082-29-1 NLP: 500-191-5 Reg.nr.: 01-2119972320-44	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine ⚠ Eye Dam. 1, H318	2.5-<5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≤0.5%

**· Additional information:**

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.**· After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.**· After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.**· 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Use neutralising agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
No special measures required.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 766 mg/m <sup>3</sup> , 400 ppm

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 4)

**64-17-5 ethanol**WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**78-83-1 iso-butanol**

WEL Short-term value: 231 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 154 mg/m<sup>3</sup>, 50 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**107-98-2 1-methoxy-2-propanol**

WEL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
Sk

**71-36-3 butan-1-ol**

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm  
Sk

**78-93-3 butanone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm  
Sk, BMGV

**· DNELs****64-17-5 ethanol**

Oral	DNEL	87 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	343 mg/kg /per day (Worker, longterm systemic)
	DNEL	206 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	950 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	1900 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	114 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	950 mg/m <sup>3</sup> (Consumer, acute local)

**xylene**

Oral	DNEL	1.6 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	180 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	211 mg/m <sup>3</sup> (Worker, longterm systemic)
	DNEL	221 mg/m <sup>3</sup> (Worker, longterm local)
	DNEL	442 mg/m <sup>3</sup> (Worker, acute systemic)
	DNEL	289 mg/m <sup>3</sup> (Worker, acute local)
	DNEL	14.8 mg/m <sup>3</sup> (Consumer, longterm systemic)
	DNEL	260 mg/m <sup>3</sup> (Consumer; acute systemic)
	DNEL	65.3 mg/m <sup>3</sup> (Consumer, longterm local)
	DNEL	260 mg/m <sup>3</sup> (Consumer, acute local)

**108-65-6 2-methoxy-1-methylethyl acetate**

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m <sup>3</sup> (Worker, longterm systemic)

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 5)

(Contd. of page )

	DNEL	33 mg/m3 (Consumer, longterm systemic)
107-98-2 1-methoxy-2-propanol		
Oral	DNEL	3.3 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	50.6 mg/kg /per day (Worker, longterm systemic)
	DNEL	18.1 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	553.5 mg/m3 (Worker, acute local)
	DNEL	369 mg/m3 (Worker, longterm systemic)
	DNEL	43.9 mg/m3 (Consumer, longterm systemic)
71-36-3 butan-1-ol		
Oral	DNEL	3.125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	310 mg/m3 (Worker, longterm local)
	DNEL	55 mg/m3 (Consumer, longterm local)
78-93-3 butanone		
Oral	DNEL	31 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	1161 mg/kg /per day (Worker, longterm systemic)
	DNEL	412 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	600 mg/m3 (Worker, longterm systemic)
	DNEL	106 mg/m3 (Consumer, longterm systemic)
· PNECs		
64-17-5 ethanol		
PNEC	0.96 mg/l (Freshwater)	
PNEC	0.79 mg/l (Seawater)	
PNEC	2.75 mg/l (Sporadic release)	
PNEC	580 mg/l (Sewage treatment plant)	
PNEC	3.6 mg/kg (Freshwater sediment)	
PNEC	2.9 mg/kg (Seawater sediment)	
PNEC	0.63 mg/kg (Soil)	
108-65-6 2-methoxy-1-methylethyl acetate		
PNEC	0.635 mg/l (Freshwater)	
PNEC	0.064 mg/l (Seawater)	
PNEC	100 mg/l (Sewage treatment plant)	
PNEC	3.29 mg/kg (Freshwater sediment)	
PNEC	0.329 mg/kg (Seawater sediment)	
PNEC	0.29 mg/kg (Soil)	
107-98-2 1-methoxy-2-propanol		
PNEC	10 mg/l (Freshwater)	
PNEC	1 mg/l (Seawater)	
PNEC	100 mg/l (Sporadic release)	
PNEC	100 mg/l (Sewage treatment plant)	
PNEC	52.3 mg/kg (Freshwater sediment)	
PNEC	5.2 mg/kg (Seawater sediment)	
PNEC	4.59 mg/kg (Soil)	
71-36-3 butan-1-ol		
PNEC	0.082 mg/l (Freshwater)	
PNEC	0.0082 mg/l (Seawater)	
PNEC	2.25 mg/l (Sporadic release)	

(Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 6)

PNEC	2476 mg/l (Sewage treatment plant)
PNEC	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
PNEC	0.015 mg/kg (Soil)

**78-93-3 butanone**

PNEC	55.8 mg/l (Freshwater)
PNEC	55.8 mg/l (Seawater)
PNEC	55.8 mg/l (Sporadic release)
PNEC	709 mg/l (Sewage treatment plant)
PNEC	284.7 mg/kg (Freshwater sediment)
PNEC	284.7 mg/kg (Seawater sediment)

**· Ingredients with biological limit values:****xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

**78-93-3 butanone**

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 7)

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

- Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	3.3 Vol % (115-10-6 dimethyl ether)
Upper:	26.2 Vol % (115-10-6 dimethyl ether)
Flash point:	Not applicable, as aerosol.
Auto-ignition temperature:	240 °C (464 °F) (115-10-6 dimethyl ether)
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C (68 °F):	4000 hPa (3000.2 mm Hg) (115-10-6 dimethyl ether)
Density and/or relative density	
Density at 20 °C (68 °F):	0.8 g/cm <sup>3</sup> (6.7 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.

#### 9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	85.3 %
VOC (EC)	---
	682.5 g/l
VOC-EU%	85.32 %
Solids content:	0.1 %
Change in condition	
Evaporation rate	Not applicable.

(Contd. on page 9)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 8)

<b>· Information with regard to physical hazard classes</b>	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	120 mg/l (rat)

##### xylene

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)

##### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)

##### 71-36-3 butan-1-ol

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 9)

Inhalative	LC50 / 4 h	17000 mg/m <sup>3</sup> (rat)
<b>78-93-3 butanone</b>		
Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	34 mg/m <sup>3</sup> (rat)
<ul style="list-style-type: none"> <li>• <b>Skin corrosion/irritation</b> Causes skin irritation.</li> <li>• <b>Serious eye damage/irritation</b> Causes serious eye damage.</li> <li>• <b>Respiratory or skin sensitisation</b> May cause an allergic skin reaction.</li> <li>• <b>11.2 Information on other hazards</b></li> </ul>		
• <b>Endocrine disrupting properties</b>		
78-93-3	butanone	List II

## SECTION 12: Ecological information

### • 12.1 Toxicity

#### • Aquatic toxicity:

##### **115-10-6 dimethyl ether**

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

##### **64-17-5 ethanol**

LC50/96h	13000 mg/l (oncorhynchus mykiss)
EC50 / 48 h	12900 mg/l (algae)
LC50 / 48 h	12340 mg/l (daphnia magna)

##### **xylene**

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

##### **108-65-6 2-methoxy-1-methylethyl acetate**

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)

##### **71-36-3 butan-1-ol**

LC50 / 96 h	1376 mg/l (fish)
-------------	------------------

##### **78-93-3 butanone**

LC50 / 48 h	308 mg/l (daphnia magna)
LC50 / 72 h	1972 mg/l (Pseudokirchneriella Subcapitata)
LC50 / 96 h	2990 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
  - **12.3 Bioaccumulative potential** No further relevant information available.
  - **12.4 Mobility in soil** No further relevant information available.
  - **12.5 Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.
  - **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
  - **12.7 Other adverse effects**
  - **Additional ecological information:**
  - **General notes:**
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 10)

*Danger to drinking water if even small quantities leak into the ground.*

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

*Must not be disposed together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packaging:**

· **Recommendation:** *Dispose of packaging according to regulations on the disposal of packagings.*

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG, IATA**



· **Class**

2.1 Gases.

· **Label**

2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 12)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 11)

· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 13)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.11.2023

Version number 2 (replaces version 1)

Revision: 02.11.2023

**Trade name: Motip Industrial 2K Epoxy Clear coat highgloss**

(Contd. of page 12)

*EUH066 Repeated exposure may cause skin dryness or cracking.*

**Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*DNEL: Derived No-Effect Level (UK REACH)*

*PNEC: Predicted No-Effect Concentration (UK REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Gas 1A: Flammable gases – Category 1A*

*Aerosol 1: Aerosols – Category 1*

*Press. Gas (Comp.): Gases under pressure – Compressed gas*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

**\* Data compared to the previous version altered.**

GB