

MOTIP Roof Paint

Ord.-no.: look at ordering information

Technical Information



Paint roof panels with the MOTIP Roof Paint. Colours are selected according to RR colour codes. Roof paint has a durable UV protection. Suitable for treated and untreated surfaces of metal, wood, glass, stones, ceramics, cardboard and coated plastics.

Quality & properties

- Good coverage
- Fast drying
- Suitable for indoor and outdoor applications
- Excellent adhesion
- Non-fading and UV-resistant
- Wear resistant and scratch free

Physical & chemical data

- Base: Acrylate copolymers
- Colourname:
 - ◊ green
 - ◊ spruce green
 - ◊ white
 - ◊ light grey
 - ◊ grey
 - ◊ dark grey
 - ◊ black
 - ◊ tile red
 - ◊ red
 - ◊ brown
 - ◊ dark brown
- Smell: Characteristic
- Degree of gloss: semi mat, 25 ±5 GU
- Efficiency: 400 ML – 1.5 m²
- Dust dry: 10 min
- Dry to touch: 30 min
- Completely dry: 60 min
- Overcoatable: 24 h
- Surfaces: Roofs
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease.
- Remove loose old lacquer and rust and sand the surface. If necessary, apply a layer of MOTIP primer suitable for the surface.
- Cover areas not to be painted.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the roof paint in several thin layers. Before applying the next layer, again shake the aerosol.
- Do not spray over synthetic paints!
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 16, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com