

## MOTIP 2K Clear Coat

Ord.-no.: 04132

### Technical Information



MOTIP 2K Clear Coat is an extremely scratch resistant 2-component clear coat. It is highly fuel resistant, resistant to U.V.-rays and weather influences. Because of its very good flow and ease of polish. Offers optimal protection for high value paintings. The hardener for the 2-component product is integrated in a cartridge inside the can. As soon as the hardener inside the can is activated, the Clear Coat has to be used within 24 hours.

#### Quality & properties

- 2K Clear Coat is a high-gloss protective lacquer from professional quality.
- UV-resistant and non-fading.
- Resistant to petrol, chemicals and weather influences.
- Scratch free and shock proof.
- Do not spray over synthetic resin paints.
- Very efficient.

#### Physical & chemical data

- Base: 2K-acrylic resin
- Colourname: no colour
- Smell: Characteristic
- Degree of gloss: high gloss, >85 GU
- Efficiency: 200 ML – 0.35 - 0.5 m<sup>2</sup>
- Dust dry: 30 min
- Dry to touch: 8 h
- Completely dry: 24 h
- Surfaces: wood, paintable plastics, metal, steel, stainless steel, aluminium, brass, copper, chrome.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Storage stability: 10 y
- Content: 200 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: The surface should be clean, dry and free of grease.
- To mix the hardener with the A component, place the can upside down on a flat surface.
- Remove the protective cap from the bottom of the can.
- Take the metal ring out of the protective cap and thread it into the pin.
- Pull out the pin on the bottom of the can as far as it will go.
- When filling a 2-K system it is essential to first mix the appropriate hardener with the lacquer before filling.
- Treatment: The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 20 to 25 centimetre.
- Use within 24 hours after activation.
- Fully dry after approx. 24 hours.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 16, 2024 – This release replaces all eventually earlier issued versions.

