

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML
- **Article number:** 04201
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Paint remover
- **Process category**
PROC7 Industrial spraying
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
European Aerosols B.V.*
Wolfraamweg 2
NL-8471 XC Wolvega
The Netherlands
Tel : +31 (0)561 694400
e-mail: sds-nl@european-aerosols.com
- *Formerly known as Motip Dupli B.V.
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**
+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** *Danger*· **Hazard-determining components of labelling:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
acetoneHydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
xylene· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds.
with amides from diethylenetriamine and tall-oil fatty acids. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 2)

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	5-<10%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351	<2.5%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%
CAS: 222716-38-3 EC number: 638-743-3	Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≤0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 3)

- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³
*total inhalable **respirable

xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

· Ingredients with biological limit values:

xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 5)

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Different according to colouring

· **Odour:**

Solvent-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.5 Vol % (106-97-8 butane (containing < 0,1 % butadiene (203-450-8)))

· **Upper:**

13 Vol % (67-64-1 acetone)

· **Flash point:**

Not applicable, as aerosol.

· **Ignition temperature:**

240 °C (464 °F) (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

3500 hPa (2625.2 mm Hg)

· **Density and/or relative density**

· **Density at 20 °C (68 °F):**

0.8 g/cm³ (6.7 lbs/gal)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Aerosol

· **Important information on protection of health and environment, and on safety.**

· **Explosive properties:**

Not determined.

· **Solvent content:**

· **Organic solvents:**

80.2 %

· **VOC (EC)**

· **VOC-EU%**

634.7 g/l

80.23 %

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 6)

· Solids content:	20.3 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

*

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

· LD/LC50 values relevant for classification:

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)

xylene

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-64-1 acetone

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

xylene

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS
 · IMDG AEROSOLS
 · IATA AEROSOLS, flammable

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.
· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.
· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Warning: Gases.

· Hazard identification number (Kemler code):

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 9)

· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** R&D legislation and regulatory advisor

- **Contact:** e-mail: sds-nl@european-aerosols.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP CAMOUFLAGE COLOUR RAL 1001 400 ML

(Contd. of page 10)

IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 • *** Data compared to the previous version altered.**

GB