

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** MOTIP HEAT RESISTANT RED 400 ML
- **Article number:** 04040
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Paint remover
- **Process category**  
PROC7 Industrial spraying  
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
European Aerosols B.V.\*  
Wolfraamweg 2  
NL-8471 XC Wolvega  
The Netherlands  
Tel : +31 (0)561 694400  
e-mail: sds-nl@european-aerosols.com
- \*Formerly known as Motip Dupli B.V.
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

#### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Aquatic Chronic 2 H411                      Toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 1)

STOT SE 3      H336      May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS02    GHS07    GHS09

**Signal word** Danger**Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

Hydrocarbons, C9, aromatics

butan-1-ol

**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

**Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<12.5%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351	5-<10%
CAS: 12001-26-2 EC number: 601-648-2	Mica substance with a Community workplace exposure limit	2.5-<5%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	2.5-<5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<2.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

\*

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

\*

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

Trade name: MOTIP HEAT RESISTANT RED 400 ML

(Contd. of page 3)

- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**106-97-8 butane (containing < 0,1 % butadiene (203-450-8))**

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

**xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk; BMGV

**13463-67-7 titanium dioxide**

WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *total inhalable **respirable
-----	---

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 4)

**12001-26-2 Mica**

WEL Long-term value:  $10 \times 0.8 \times \text{mg/m}^3$   
 \*total inhalable \*\*respirable

**71-36-3 butan-1-ol**

WEL Short-term value:  $154 \text{ mg/m}^3$ , 50 ppm  
 Sk

**· Ingredients with biological limit values:****xylene**

BMGV 650 mmol/mol creatinine  
 Medium: urine  
 Sampling time: post shift  
 Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 5)

· **Eye/face protection**

Tightly sealed goggles

\*

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Physical state**

Aerosol

· **Colour:**

Different according to colouring

· **Odour:**

Solvent-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**· **Lower:**

0.6 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane)

· **Upper:**

10.9 Vol % (74-98-6 propane)

· **Flash point:**

Not applicable, as aerosol.

· **Ignition temperature:**

&gt;200 °C (&gt;392 °F) (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane)

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

3500 hPa (2625.2 mm Hg)

· **Density and/or relative density**· **Density at 20 °C (68 °F):**0.7 g/cm<sup>3</sup> (5.8 lbs/gal)· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**· **Appearance:**· **Form:**

Aerosol

· **Important information on protection of health and environment, and on safety.**· **Explosive properties:**

Not determined.

· **Solvent content:**· **Organic solvents:**

85.4 %

· **VOC (EC)**

---

· **VOC-EU%**598.0 g/l  
85.44 %· **Solids content:**

14.5 %

· **Change in condition**· **Evaporation rate**

Not applicable.

· **Information with regard to physical hazard classes**· **Explosives**

Void

(Contd. on page 7)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 6)

· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

#### · **LD/LC50 values relevant for classification:**

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

##### **xylene**

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)

##### **71-36-3 butan-1-ol**

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 8)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 7)

### · 11.2 Information on other hazards

#### · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h 30-100 mg/l (algae)

LC50 / 96 h 11.4 mg/l (fish)

##### xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50 / 96 h 13.5 mg/l (fish)

##### 71-36-3 butan-1-ol

LC50 / 96 h 1376 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

### · 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### · 12.7 Other adverse effects

· Remark: Toxic for fish

### · Additional ecological information:

#### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packaging:

#### · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

## SECTION 14: Transport information

### · 14.1 UN number or ID number

#### · ADR, IMDG, IATA

UN1950

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 8)

· **14.2 UN proper shipping name**· **ADR**1950 AEROSOLS, ENVIRONMENTALLY  
HAZARDOUS· **IMDG**

AEROSOLS, MARINE POLLUTANT

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG**· **Class**

2.1 Gases.

· **Label**

2.1

· **IATA**· **Class**

2.1 Gases.

· **Label**

2.1

· **14.4 Packing group**· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**· **Marine pollutant:**

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 9)

· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**
- **Regulation (EC) No 273/2004 on drug precursors**  
None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 04.08.2022

Version number 60 (replaces version 59)

Revision: 30.03.2022

**Trade name: MOTIP HEAT RESISTANT RED 400 ML**

(Contd. of page 10)

- H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Contact:** e-mail: [sds-nl@european-aerosols.com](mailto:sds-nl@european-aerosols.com)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**

GB