

## MOTIP Leather & Vinyl Paint

Ord.-no.: look at ordering information

### Technical Information



Repair and embellish vinyl, leather and artificial leather parts of your car such as car seats with MOTIP Leather Paint. Leather Paint has a lasting colour and lasting gloss and maintains the original structure.

#### Quality & properties

- Lasting colour and lasting gloss
- Elastic
- Excellent adhesion
- Maintains the original structure

#### Physical & chemical data

- Base: Nitrocellulose resin
- Colourname:
  - ◊ grey
  - ◊ brown
  - ◊ white
  - ◊ beige
  - ◊ beige brown
  - ◊ beige grey
  - ◊ black
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 200 ML – 1 m<sup>2</sup>
- Dry to touch: 10 - 20 min
- Dust dry: 5 - 10 min
- Completely dry: 120 min
- Overcoatable: 120 min
- Surfaces: Vinyl, leather and artificial leather
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: – 50 °C
- Storage stability:
  - ◊ 10 y
  - ◊ 5 y
- Content: 200 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease.
- Non-treated parts should be covered.
- The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample.
- Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the vinyl spray in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 17, 2022** – This release replaces all eventually earlier issued versions.

**European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)**  
**European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)**