

MOTIP Camouflage Paint

Ord.-no.: look at ordering information

Technical Information



Use MOTIP Camouflage Paint to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, textile and various types of plastic.

Quality & properties

- Excellent coverage and filling property
- Lasting colour and gloss
- Scratch free and shock proof
- Resistant to petrol, chemicals and weather influences
- Corrosion preventive
- Excellent adhesion

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - ◊ beige
 - ◊ green
 - ◊ grey
 - ◊ brown
 - ◊ black
- Smell: Characteristic
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 400 ML – 1.75 m²
- Dry to touch: 45 min
- Dust dry: 10 - 20 min
- Completely dry: 16 h
- Overcoatable: 16 h
- Surfaces: Wood, metal, aluminium, glass, stone, textile and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- Even when the lacquer has hardened, do not treat with acrylic lacquer or nitro-cellulose lacquer.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline

1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 17, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com