

## MOTIP Wheel Protect Wax

Ord.-no.: 000733

### Technical Information



Protect your rims and hubcaps with MOTIP Wheel Protect Wax. Wheel Protect Wax gives a glossy result, reduces the adhesion of dirt, is free from solvents, is pH-neutral and contains silicones.

#### Quality & properties

- Reduces the adhesion of dirt
- Gives a glossy result
- Free from solvents
- pH-neutral
- Contains silicones
- User-friendly

#### Physical & chemical data

- Base: PE Wax
- Colourname: white
- Smell: Characteristic
- Surfaces: Rims, hubcaps
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 23/20 bar
- pH-Value: 8,5
- Flash point: >100 °C
- Storage stability: 10 y
- Content: 500 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly. Store frost-free.
- The surface should be clean and dry.
- When desired, clean the rims or the hubcaps with MOTIP Wheel Cleaner.
- Apply Wheel Protect Wax in a thin, equal layer and polish with a soft cloth.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 17, 2022** – This release replaces all eventually earlier issued versions.