

## MOTIP Hammerfinish Paint

Ord.-no.: look at ordering information

## Technical Information



Fast-drying paint with hammered effect for treated and untreated surfaces including wood, metal, aluminium, glass and plastic. MOTIP Hammerfinish Paint offers good coverage, is shock proof and is resistant to scratches, petrol, chemicals, thinned cleaners and weather influences.

### Quality & properties

- Fast drying
- Good coverage
- Scratch free and shock proof
- Resistant to petrol, chemicals, thinned cleaners and weather influences

### Physical & chemical data

- Base: Alkyd resin
- Colourname:
  - ◊ silver
  - ◊ blue
  - ◊ green
  - ◊ grey
  - ◊ gold
  - ◊ anthracite
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 1.25 - 1.75 m<sup>2</sup>
- Dry to touch: 10 - 20 min
- Dust dry: 5 - 10 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: Wood, metal, aluminium, glass, stone and various types of plastic.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Temperature Resistance: – 110 °C
- Storage stability: 10 y
- Content: 400 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MOTIP primer suitable for the surface. After drying, sand the base layer (grain 600).
- Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply a thin first layer and after several minutes apply a finishing coat. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of August 17, 2022** – This release replaces all eventually earlier issued versions.

**European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)**  
**European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)**