

MOTIP De-Icer Extreme

Ord.-no.: 000791

Technical Information



Easily remove frost at extreme temperatures from windows, door locks and the boot of the car with MOTIP De-Icer Extreme. The spray contains anti-freeze, which prevents re-freezing of the surface. De-Icer Extreme does not affect rubber, lacquer or chrome.

Quality & properties

- Prevents re-freezing
- Fast acting
- Does not affect rubber, lacquer or chrome
- Contains anti-freeze

Physical & chemical data

- Base: Alcohol
- Colourname: transparent
- Smell: Characteristic
- Vapour pressure: 8500/20 bar
- Flash point: 13 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Before use, shake the aerosol
- Apply equally, horizontally from top to bottom.
- Allow to take effect until the ice has disappeared.
- To prevent re-freezing, only remove the applied product when the vehicle has warmed up.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 17, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com